

TECHNICAL FEATURES

BICOLOUR PS

DIMENSIONS



Thickness:	from 400 to 1700 μ*
Width:	from 163 to 1200 mm*
Reel diameter:	from 580 to 1200 mm in pallets from 1700 to 2200 mm on pedestal
Core diameter:	152 or 200 mm* 400 mm on pedestal

* extreme values: to confirm according to width/thickness ratio
THE TECHNICAL FEASIBILITY OF EACH PRODUCT MUST BE VALIDATED BY CEDAP

COLOUR



See **STANDARD COLOUR LIST**

- + Colour Countertype for special manufacturing orders above 100 t.
- + Unpolished or glossy (plaxé) finish.

QUANTITY



Minimum production: **5 t**
(same width and thickness)

MECHANICAL FEATURES



Rigidity, shock resistance, cold and heat resistance are criteria that must be determined according to the packaging features and to thermoforming machine used.
Cedap technical assistance is at our customers' disposal for production optimization.

CEDAP



Non-contractual simulation

PALLETIZATION

WITHOUT CORE:

- possible

PALLETS:

(horizontal or vertical core)

- 600 x 1200 mm
- 730 x 730 mm
- 760 x 760 mm
- 800 x 800 mm
- 800 x 1200 mm
- 940 x 1200 mm
- 1000 x 1000 mm
- 1000 x 1200 mm
- 1100 x 1100 mm
- 1200 x 1200 mm

PEDESTALS:

(double or mono-width)

- possible