

## TECHNICAL FEATURES

# TWIN POT PS

### DIMENSIONS



Thickness: **from 500 to 1400  $\mu$ \***

Width: **from 214 to 800 mm\***

Reel diameter: **from 580 to 1200 mm in pallets**

Core diameter: **152 or 200 mm\***

\* extreme values: to confirm according to width/thickness ratio.  
Product that can need a specific technical development according to the thickness and width of stripes  
THE TECHNICAL FEASIBILITY OF EACH PRODUCT MUST BE VALIDATED BY CEDAP

### COLOUR



See **STANDARD COLOUR LIST**

+ Colour Countertype for special manufacturing orders above 100 t.

+ Unpolished or glossy (plaxé) finish.

### QUANTITY



Minimum production: **5 t**  
(same width and thickness)

### MECHANICAL FEATURES



Rigidity, shock resistance, cold and heat resistance are criteria that must be determined according to the packaging features and to thermoforming machine used.  
Cedap technical assistance is at our customers' disposal for production optimization.

# CEDAP



Non-contractual simulation

### PALLETIZATION

#### WITHOUT CORE:

- possible

#### PALLETS:

(horizontal or vertical core)

- 600 x 1200 mm
- 730 x 730 mm
- 760 x 760 mm
- 800 x 800 mm
- 800 x 1200 mm
- 940 x 1200 mm
- 1000 x 1000 mm
- 1000 x 1200 mm
- 1100 x 1100 mm
- 1200 x 1200 mm

#### PEDESTALS:

(double or mono-width)

- not possible